



Workstation WS3



Workstation WS3

WS3 workstation, specifically designed for the L3 autonomous scrubber dryer, aimed at simplifying the maintenance process and significantly improving robot performance.

Features & Benifits

- **Comprehensive Service:**

One-stop realization of auto charging, water refilling, drainage, and detergent filling, achieving fully automated maintenance.

- **Efficient 24/7 Operation:**

Upgraded to 40A high output power, enabling the robot to run continuously 24/7.

- **Minimal Human Intervention:**

Drastically reduces maintenance work, achieving true automated cleaning, reducing costs and increasing efficiency.

Technical Data



Dimensions(L*W*H)

16.1*10.1*27.6 in | 409*256*700 mm



Input Voltage

100~240 V a.c



Output Voltage

28.8 V d.c



Weight

84 lbs | 38 kg



Max. Power

1.88 hp | 1400 W



Operating Temperature

32°F~113°F | 0°C~45°C

Available for the

L3





Mobile Water Tank WT3



Mobile Water Tank WT3

WT3 is an optional operational accessory designed to function as a mobile off-station extension of the workstation WS3. Engineered with a high-capacity 16gal/60L fresh water tank and a corresponding wastewater tank, this system directly addresses and resolves the logistical inconvenience of connecting water hoses to a fixed workstation in unplumbed or inconvenient locations.

Features & Benifits

- **Hose-Free Setup:**

Eliminates plumbing constraints, bypassing direct host-station hose connections in any location.

- **Extended Runtime:**

High water capacity enables continuous, uninterrupted cleaning operations.

- **Operational Flexibility:**

Expands cleaning coverage efficiently to areas without plumbing connections.

Technical Data



Dimensions(L*W*H)

23.6*22.7*38.1 in | 600*577*966 mm



Clean Water Tank

16 gal | 60 L



Waster Water Tank

13.2 gal | 50 L



Weight

62 lbs | 28 kg



Input Voltage

24 V d.c.



Water Temperature

34°F~104°F | 1°C~40°C

Available for the

L3

